Amendments to the Claims:

Claims 1-73 were originally pending in this application. Claims 14-20, 41-53 and 67-73 are withdrawn from consideration. As a result, claims 1-13, 21-40 and 54-66 are currently pending. Claims 1, 21, 31 and 54 are independent.

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1 (CURRENTLY AMENDED): A method of managing a photographing condition of an image sensing apparatus by a user, comprising:

a displaying step of displaying an image photographed by the image sensing apparatus and an associated photographing condition [[in]] represented by values used for controlling the image sensing apparatus for photographing the image;

an image selection step of selecting the image by the user while the user monitors the image; and

a first storage step of storing the image and the associated photographing condition upon receiving a request from the user.

2 (ORIGINAL): The method according to claim 1, further comprising: an input step of inputting a photographing status of the image selected in said image selection step; and

a second storage step of storing the photographing status input in said input step in association with the selected image.

3 (ORIGINAL): The method according to claim 1, further comprising: a reception step of receiving one or more images and a photographing condition in photographing each image from the image sensing apparatus, wherein said image selection step comprises selecting one image from images received in said reception step.

4 (ORIGINAL):   The method according to claim 1, wherein said first storage step comprises

storing the image and photographing condition in memory of a control apparatus of the image

sensing apparatus.

5 (ORIGINAL):   The method according to claim 1, wherein said first storage step comprises

storing the image and photographing condition in an external storage medium.

6 (ORIGINAL):   The method according to claim 2, wherein said second storage step

comprises storing the photographing status in memory of a control apparatus of the image

sensing apparatus.

7 (ORIGINAL):   The method according to claim 2, wherein said second storage step

comprises storing the photographing status in an external storage medium.

8 (ORIGINAL):   The method according to claim 1, further comprising: a condition

selection step of selecting a desired photographing condition from photographing conditions that

are stored in association with respective images in said first storage step; and a transfer step of

transferring the photographing condition selected in said condition selection step to the image

sensing apparatus.

9 (ORIGINAL):   The method according to claim 8, wherein said condition selection step

comprises selecting a photographing condition by designating a desired image.

857682 v1

10 (ORIGINAL): The method according to claim 8, wherein said condition selection step comprises selecting a photographing condition by designating values of some of a plurality of setting items of the photographing condition.

11 (ORIGINAL): The method according to claim 8, further comprising: a partial selection step of selecting some of a plurality of setting items of the photographing condition selected in the condition selection step, wherein said transfer step comprises transferring only the photographing condition setting items selected in said partial selection step.

12 (ORIGINAL): The method according to claim 2, further comprising: a condition selection step of selecting a desired photographing condition from photographing conditions that are stored in association with respective images in said first storage step; and a transfer step of transferring the photographing condition selected in said condition selection step to the image sensing apparatus.

13 (ORIGINAL): The method according to claim 12, wherein said condition selection step comprises selecting a photographing condition by designating a photographing status.

14 (WITHDRAWN): A method of setting a photographing condition in an image sensing apparatus, comprising:

a condition selection step of selecting a desired photographing condition from photographing conditions that are stored in association with respective images in a storage medium; and

a transfer step of transferring the photographing condition selected in said condition selection step to the image sensing apparatus.

15 (WITHDRAWN): The method according to claim 14, wherein said condition selection step

comprises selecting a photographing condition by designating a desired image.

16 (WITHDRAWN): The method according to claim 14, wherein said condition selection step

comprises selecting a photographing condition by designating some of a plurality of setting items

of the photographing condition.

17 (WITHDRAWN): The method according to claim 14, wherein said storage medium stores

photographing statuses in photographing the respective images, and said condition selection step

comprises selecting a photographing condition by designating a photographing status.

18 (WITHDRAWN): The method according to claim 14, further comprising: a partial selection

step of selecting some of a plurality of setting items of the photographing condition selected in

the condition selection step, wherein said transfer step comprises transferring only the

photographing condition setting items selected in said partial selection step.

19 (WITHDRAWN): A method of setting a photographing condition of an image sensing

apparatus, comprising:

a display step of displaying a plurality of arbitrary photographing conditions

stored in a storage medium;

a condition selection step of selecting a desired photographing condition from the

plurality of photographing conditions displayed in said display step; and

a setting step of setting the photographing condition selected in said condition

selection step in the image sensing apparatus.

857682 v1

20 (WITHDRAWN): The method according to claim 19, wherein each photographing condition

has a plurality of changeable setting items.

21 (CURRENTLY AMENDED):   An image sensing apparatus comprising:

a display configured to display an image photographed by the image sensing

apparatus and an associated photographing condition [[in]] represented by values used for

controlling the image sensing apparatus for photographing the image;

an image selector configured to select the image by a user while the user monitors

the image; and

a storage device configured to store the image and the associated photographing

condition upon receiving a request from the user.

22 (PREVIOUSLY PRESENTED): The image sensing apparatus according to claim 21, further

comprising: an input device configured to input a photographing status of the image selected by

said image selector, wherein said storage device stores the photographing status input by said

input device in association with the selected image.

23 (PREVIOUSLY PRESENTED): The image sensing apparatus according to claim 21,

wherein said storage device stores the image and photographing condition in internal memory.

24 (PREVIOUSLY PRESENTED): The image sensing apparatus according to claim 21,

wherein said storage device stores the image and photographing condition in an external storage

medium.

25 (PREVIOUSLY PRESENTED): The image sensing apparatus according to claim 21, further

comprising: a condition selector configured to select a desired photographing condition from

photographing conditions that are stored in association with respective images in said storage

device; and a setting device configured to set the photographing condition selected by said

condition selector.

26 (PREVIOUSLY PRESENTED): The image sensing apparatus according to claim 25,

wherein said condition selector selects a photographing condition by designating a desired image.

27 (PREVIOUSLY PRESENTED): The image sensing apparatus according to claim 25,

wherein said condition selector selects a photographing condition by designating values of some

of a plurality of setting items of the photographing condition.

28 (PREVIOUSLY PRESENTED): The image sensing apparatus according to claim 25, further

comprising: a partial selector configured to select some of a plurality of setting items of the

photographing condition selected in by said condition selector, wherein said setting device sets

only the photographing condition setting items selected by said partial selector.

29 (PREVIOUSLY PRESENTED): The image sensing apparatus according to claim 22, further

comprising: a condition selector configured to select a desired photographing condition from

photographing conditions that are stored in association with respective images by said storage

device; and a setting device configured to set the photographing condition selected by said

condition selector.

7

30 (PREVIOUSLY PRESENTED): The image sensing apparatus according to claim 29,

wherein said condition selector selects a photographing condition by designating a

photographing status.

31 (CURRENTLY AMENDED):   A control apparatus for controlling an image sensing

apparatus by a user, comprising:

         a display that displays an image photographed by the image sensing apparatus and

an associated photographing condition [[in]] represented by values used for controlling the image

sensing apparatus for photographing the image;

         an image selector that selects the image by the user while the user monitors the

image; and

         a storage device that stores the image and the associated photographing condition

upon receiving a request from the user.

32 (PREVIOUSLY PRESENTED): The control apparatus according to claim 31, further

comprising: an input device that inputs a photographing status of the image selected by said

image selector, wherein said storage device stores the photographing status input by said input

device in association with the selected image.

33 (PREVIOUSLY PRESENTED): The control apparatus according to claim 31, wherein said

storage device stores the image and photographing condition in internal memory.

34 (PREVIOUSLY PRESENTED): The control apparatus according to claim 31, wherein said

storage device stores the image and photographing condition in an external storage medium.

857682 v1

35(PREVIOUSLY PRESENTED):   The control apparatus according to claim 31, further

comprising: a condition selector that selects a desired photographing condition from

photographing conditions that are stored in association with respective images in said storage

device; and a transfer device that transfers the photographing condition selected by said

condition selector to the image sensing apparatus.

36 (PREVIOUSLY PRESENTED):   The control apparatus according to claim 35, wherein said

condition selector selects a photographing condition by designating a desired image.

37 (PREVIOUSLY PRESENTED):   The control apparatus according to claim 35, wherein said

condition selector selects a photographing condition by designating values of some of a plurality

of setting items of the photographing condition.

38 (PREVIOUSLY PRESENTED):   The control apparatus according to claim 35, further

comprising: a partial selector that selects some of a plurality of setting items of the

photographing condition selected by said condition selector, wherein said setting device sets only

the photographing condition setting items selected by said partial selector.

39 (PREVIOUSLY PRESENTED):   The control apparatus according to claim 32, further

comprising: a condition selector that selects a desired photographing condition from

photographing conditions that are stored in association with respective images by said storage

device; and a transfer device that transfers the photographing condition selected by said

condition selector to the image sensing apparatus.

857682 v1

40 (PREVIOUSLY PRESENTED):   The control apparatus according to claim 39, wherein said

condition selector selects a photographing condition by designating a photographing status.

41 (WITHDRAWN): A control apparatus for controlling an image sensing apparatus,

comprising: condition selection means for selecting a desired photographing condition from

photographing conditions that are stored in association with respective images in a storage

medium; and transfer means for transferring the photographing condition selected by said

condition selection means to the image sensing apparatus.

42(WITHDRAWN):   The control apparatus according to claim 41, wherein said condition

selection means selects a photographing condition by designating a desired image.

43(WITHDRAWN):   The control apparatus according to claim 41, wherein said condition

selection means selects a photographing condition by designating some of a plurality of setting

items of the photographing condition.

44(WITHDRAWN):   The control apparatus according to claim 41, wherein the storage medium

stores photographing statuses in photographing the respective images, and said condition

selection means selects a photographing condition by designating a photographing status.

45 (WITHDRAWN): The control apparatus according to claim 41, further comprising: partial

selection means for selecting some of a plurality of setting items of the photographing condition

selected by said condition selection means, wherein said transfer means transfers only the

photographing condition setting items selected by said partial selection means.

857682 v1

46 (WITHDRAWN): An image sensing apparatus comprising:

      display means for displaying a plurality of arbitrary photographing conditions stored in a storage medium;

      condition selection means for selecting a desired photographing condition from the plurality of photographing conditions displayed by said display means; and

      setting means for setting the photographing condition selected by said condition selection means in said image sensing apparatus.

47 (WITHDRAWN): The image sensing apparatus according to claim 46, wherein each photographing condition has a plurality of changeable setting items, further comprising: change means for changing the setting items; and storage means for storing the setting items changed by said change means in the storage medium.

48 (WITHDRAWN): The image sensing apparatus according to claim 46, wherein the storage medium is internal memory.

49 (WITHDRAWN): The image sensing apparatus according to claim 46, wherein the storage medium is an external storage medium.

50 (WITHDRAWN): A control apparatus for controlling an image sensing apparatus, comprising:

      display means for displaying a plurality of arbitrary photographing conditions stored in a storage medium; condition selection means for selecting a desired photographing condition from the plurality of photographing conditions displayed by said display means; and

857682 v1

setting means for transferring the photographing condition selected by said

condition selection means to the image sensing apparatus.

51 (WITHDRAWN): The control apparatus according to claim 50, wherein each photographing

condition has a plurality of changeable setting items, further comprising: change means for

changing the setting items; and storage means for storing the setting items changed by said

change means in the storage medium.

52 (WITHDRAWN): The control apparatus according to claim 50, wherein the storage medium

is internal memory.

53 (WITHDRAWN): The control apparatus according to claim 50, wherein the storage medium

is an external storage medium.

54 (CURRENTLY AMENDED):   A computer readable program for managing a

photographing condition of an image sensing apparatus by a user, comprising:

a first computer readable code for displaying an image photographed by the image

sensing apparatus and an associated photographing condition [[in]] represented by values used

for controlling the image sensing apparatus for photographing the image;

a second computer readable code for selecting the image by the user while the

user monitors the image; and

a third computer readable code for storing the selected image and the associated

photographing condition upon receiving a request from the user.

55 (PREVIOUSLY PRESENTED): The program according to claim 54, further comprising: a fourth computer readable code for inputting a photographing status of the selected image; and a fifth computer readable code for storing the input photographing status in association with the selected image.

56 (PREVIOUSLY PRESENTED): The program according to claim 54, further comprising: a fourth computer readable code for receiving one or more images and a photographing condition in photographing each image from the image sensing apparatus, wherein the second computer readable code selects one image from the received images.

57 (PREVIOUSLY PRESENTED): The program according to claim 54, wherein the third computer readable code causes the image and photographing condition stored in memory of a control apparatus of the image sensing apparatus.

58 (PREVIOUSLY PRESENTED): The program according to claim 54, wherein the third computer readable code causes the image and photographing condition stored in an external storage medium.

59 (PREVIOUSLY PRESENTED): The program according to claim 55, wherein the fifth computer readable code causes the photographing status stored in memory of a control apparatus of the image sensing apparatus.

60 (PREVIOUSLY PRESENTED): The program according to claim 55, wherein the fifth computer readable code causes the photographing status stored in an external storage medium.

13

61 (PREVIOUSLY PRESENTED): The program according to claim 54, further comprising: a

fourth computer readable code for selecting a desired photographing condition from

photographing conditions that are stored in association with respective images by the second

computer readable code; and a fifth computer readable code for transferring the selected

photographing condition to the image sensing apparatus.

62 (PREVIOUSLY PRESENTED): The program according to claim 61, wherein the fourth

computer readable code selects a photographing condition by designating a desired image.

63 (PREVIOUSLY PRESENTED): The program according to claim 61, wherein the fourth

computer readable code selects a photographing condition by designating values of some of a

plurality of setting items of the photographing condition.

64 (PREVIOUSLY PRESENTED): The program according to claim 61, further comprising: a

sixth computer readable code for selecting some of a plurality of setting items of the selected

photographing condition, wherein the fourth computer readable code transfers only the

photographing condition setting items selected by the fifth computer readable code.

65 (PREVIOUSLY PRESENTED): The program according to claim 55, further comprising: a

sixth computer readable code for selecting a desired photographing condition from

photographing conditions that are stored in association with respective images by the fourth

computer readable code; and a seventh computer readable code for transferring the selected

photographing condition to the image sensing apparatus.

66 (PREVIOUSLY PRESENTED):   The program according to claim 65, wherein the sixth

computer readable code selects a photographing condition by designating a photographing status.

67 (WITHDRAWN): A computer readable program for setting a photographing condition in an

image sensing apparatus, comprising:

a first computer readable code for selecting a desired photographing condition

from photographing conditions that are stored in association with respective images in a storage

medium; and

a second computer readable code for transferring the selected photographing

condition to the image sensing apparatus.

68 (WITHDRAWN): The program according to claim 67, wherein the first computer readable

code selects a photographing condition by designating a desired image.

69 (WITHDRAWN): The program according to claim 67, wherein the first computer readable

code selects a photographing condition by designating some of a plurality of setting items of the

photographing condition.

70 (WITHDRAWN): The program according to claim 67, wherein the storage medium stores

photographing statuses in photographing the respective images, and the first computer readable

code selects a photographing condition by designating a photographing status.

71 (WITHDRAWN): The program according to claim 67, further comprising: a third computer

readable code for selecting some of a plurality of setting items of the selected photographing

condition, wherein the second computer readable code transfers only the photographing

condition setting items selected by the third computer readable code.

72 (WITHDRAWN): A computer readable program for setting a photographing condition of an

image sensing apparatus, comprising:

a first computer readable code for displaying a plurality of arbitrary

photographing conditions stored in a storage medium;

a second computer readable code for selecting a desired photographing condition

from the plurality of displayed photographing conditions; and

a third computer readable code for setting the selected photographing condition in

the image sensing apparatus.

73 (WITHDRAWN): The program according to claim 72, wherein each photographing

condition has a plurality of changeable setting items.

16